# Δ

## FIOMAX Diesel Fueling System


#### Application:

· designed for on-site refueling of construction, mining, forestry and agricultural equipment

#### **Diesel Fuel Nozzles**

#### Features:

- 1½" female NPT
- tested to 180 gallons per minute
- · integrated high flow swivel and sealing plug
- plug/bumper assembly gives complete nose seal
- investment cast aluminum housing
- · anodized aluminum non-wear parts
- stainless steel wear components
- Delron® bushings eliminate metal-to-metal wear
- interchanges with Caterpillar® and Wiggins systems





#### **One-Piece Diesel Fuel Receivers**

#### Features:

- 2" male NPT
- O-ring sealed aluminum cap
- · cap has set screw attached vinyl coated cable lanyard

Description	Material	Part #
one-piece receiver without cap	nickel-plated steel	FRS
one-piece receiver with cap	nickel-plated steel	FRS-C
one-piece receiver without cap	anodized aluminum	FRA
one-piece receiver with cap	anodized aluminum	FRA-C
cap for receiver	anodized aluminum	FR-CAP



#### **Two-Piece Diesel Fuel Receivers**

### Features:

- 2" male NPT
- · O-ring sealed aluminum cap
- · cap has set screw attached vinyl coated cable lanyard

Description	Part #
two-piece receiver with removable stainless sleeve, without cap	FR-RS
two-piece receiver with removable stainless sleeve with cap removable sleeve replacement for two-piece receiver cap for receiver	FR-RS-C FR-RS-R FR-CAP

