

BRAID HYDRAULIC HOSE

TWO WIRE BRAID HYDRAULIC HOSE

SUPER-REX HOSE (KS2)



Part No	ID			OD		Operating pressure		Burst pressure		Bend radius		Weight	
	Dash	inch	mm	inch	mm	bar	psi	bar	psi	mm	inch	lbs/ft	kg/m
312-4	4	1/4"	6.4	0.52	13.1	450	6530	1800	26100	45	1.77	0.18	0.27
312-5	5	5/16"	7.9	0.58	14.7	420	6090	1680	24360	55	2.17	0.21	0.32
312-6	6	3/8"	9.5	0.67	17.1	385	5590	1540	22330	65	2.56	0.26	0.39
312-8	8	1/2"	12.5	0.80	20.3	345	5010	1380	20010	80	3.15	0.35	0.53
312-10	10	5/8"	15.8	0.97	24.7	320	4640	1280	18560	90	3.54	0.48	0.72
312-12	12	3/4"	19.0	1.09	27.7	300	4350	1200	17400	120	4.72	0.58	0.86
312-16	16	1"	25.4	1.33	35.8	225	3270	900	13050	160	6.30	0.88	1.31
312-20	20	1-1/4"	31.8	1.71	43.5	175	2540	700	10150	300	11.81	1.14	1.70

- Tube** : Oil Resistant Synthetic Rubber
- Cover** : Abrasion, ozone, Oil and weather resistant synthetic rubber
- Reinforcement** : Two wire braid of high tensile steel wire
- Temperature** : -40°C to +100°C (-40°F to +212°F) Hot air Max.70°C

Fittings - 7 Series

