

BRAID HYDRAULIC HOSE

TWO WIRE BRAID HYDRAULIC HOSE

SAE 100 R2AT / 2SN DIN EN 853



Part No	ID			OD		Operating pressure		Burst pressure		Bend radius		Weight	
	Dash	inch	mm	inch	mm	psi	par	bar	bar	inch	mm	lbs/ft	kg/m
327-4	4	1/4"	6.4	0.49	12.5	5800	400	23200	1600	3.94	100	0.22	0.33
327-6	6	3/8"	9.5	0.66	16.7	4800	330	19140	1320	4.92	125	0.36	0.54
327-8	8	1/2"	12.5	0.78	19.9	4000	275	15950	1100	7.09	180	0.42	0.63
327-10	10	5/8"	15.8	0.91	23.0	3625	250	14500	1000	8.07	205	0.52	0.77
327-12	12	3/4"	19.0	1.07	27.1	3100	215	12470	860	9.45	240	0.65	0.96
327-16	16	1"	25.4	1.38	35.1	2400	165	9570	660	11.81	300	0.95	1.41
327-20	20	1-1/4"	31.8	1.75	44.4	1820	125	7250	500	16.54	420	1.26	1.87
327-24	24	1-1/2"	38.1	2.00	50.8	1310	90	5220	360	19.69	500	1.50	2.23
327-32	32	2"	51.0	2.50	63.5	1160	80	4640	320	24.80	630	1.94	2.88

- Tube** : Oil Resistant Synthetic Rubber
- Cover** : Abrasion, ozone, Oil and weather resistant synthetic rubber
- Reinforcement** : Two wire braid of high tensile steel wire
- Temperature** : -40°C to +100°C (-40°F to +212°F) Hot air Max.70°C

Fittings – 7 Series

