

SPIRAL HYDRAULIC HOSE

FOUR WIRE 4000 PSI HYDRAULIC HOSE

EXCEEDS SAE100R12



Part No	ID			OD		Operating pressure		Burst pressure		Bend radius		Weight	
	Dash	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	lbs/ft	kg/m
408-6	6	3/8"	9.5	0.77	19.5	4060	280	16240	1120	2.56	65	0.43	0.52
408-8	8	1/2"	12.5	0.88	22.3	4060	280	16240	1120	3.54	90	0.56	0.60
408-10	10	5/8"	15.8	1.04	26.4	4060	280	16240	1120	3.94	100	0.69	0.78
408-12	12	3/4"	19.0	1.21	30.7	4060	280	16240	1120	4.72	120	0.82	1.13
408-16	16	1"	25.4	1.49	37.8	4060	280	16240	1120	5.91	150	1.20	1.65

Tube : Oil Resistant Synthetic Rubber

Cover : Abrasion, ozone, Oil and weather resistant synthetic rubber

Reinforcement : Four spiral layers of high tensile steel wire

Temperature : -40°C to +100°C (-40°F to +212°F) Hot air Max.70°C

Fittings – 7 Series

