

## Premium Duty Spring Retractable Hose Reels

**Air/Water/Oil/Grease** - 1/4", 3/8", 1/2", 3/4" I.D.

- Robust and ideal for the most demanding applications
- Individually powder coated components offer maximum protection from premature corrosion
- Full flow swivel combines the highest grade seal design and materials with bearing areas for maximum service life
- Base and guide arm are formed from high-grade steel and engineered with structural forms and gussets to yield the greatest amount of strength
- Inlet hose is plumbed into the base to eliminate the risk of stress on the swivel
- Guide arm adjusts to seven positions



7650 OLP



### Additional Series 7000 Models

- Enclosed Reels** - Page 11
- Stainless Steel** - Page 19
- Fuel/DEF** - Page 20-21
- Twin Hydraulic** - Page 22
- Pressure Wash** - Page 23
- Garden Reels** - Page 24
- Cord Reels** - Page 30
- Gas/Cable Welding** - Page 34-37



7600 OLP



7850 CLP



7650 OLP

Model with hose & bumper	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Max Pressure		NPT(M) Hose Outlet	NPT(F) Reel Inlet	NPT(F) Reel Outlet
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in	in
<b>Low Pressure Air/Water Reels</b> Maximum Temperature 150 °F (65 °C) Max working pressure is at 70 °F (20 °C)													
7650 OLP	43	20	3/8	10	.600	15	50	15	300	21	1/4	1/2	1/2
7670 OLP	47	21	3/8	10	.600	15	70	22	300	21	1/4	1/2	1/2
7850 OLP	47	21	1/2	13	.750	19	50	15	300	21	3/8	1/2	1/2
7850 CLP*	57	26	1/2	13	.750	19	50	15	300	21	3/8	1/2	1/2
7850 OLP121	47	21	1/2	13	.750	19	50	15	300	21	1/2	1/2	1/2
7925 OLP	47	21	3/4	19	1.075	27	25	8	250	17	3/4	3/4	3/4
<b>Medium Pressure Oil Reels</b> Maximum Temperature 210 °F (99 °C)													
7650 OMP	55	25	3/8	10	.690	18	50	15	2600	179	3/8	1/2	1/2
7850 OMP	57	26	1/2	13	.820	21	50	15	3000	207	1/2	1/2	1/2
<b>High Pressure Grease Reels</b> Maximum Temperature 210 °F (99 °C)													
7450 OHP	55	25	1/4	6	.580	15	50	15	5000	345	1/4	1/2	3/8
7650 OHP	60	27	3/8	10	.730	19	50	15	4800	331	1/4	1/2	3/8
Low pressure reels furnished standard with PVC hose. Medium pressure reels furnished standard with S.A.E. 100R1-AT (3/8") or S.A.E. 100R17 (1/2") one wire braid hose. High pressure reels furnished standard with S.A.E. 100 R2T two wire braid hose. *Cabinet style reel - guide arm not included; inlet hose is included													

Dimensions					
	A	B	C	D	E
in	20 <sup>1</sup> / <sub>4</sub>	19 <sup>3</sup> / <sub>4</sub>	7 <sup>13</sup> / <sub>16</sub>	3 <sup>7</sup> / <sub>8</sub>	7
mm	514	502	198	98	178

Model without hose & bumper	Shipping Weight		Hose Capacity			Max Pressure	NPT(F) Reel Inlet	NPT(F) Reel Outlet
	lbs	kg	I.D.	O.D.	Length			
			in	mm	in	mm	ft	m
<b>Low Pressure Air/Water Reels</b> Maximum Temperature 210 °F (99 °C)								
7600 OLP	40	18	3/8	10	.600	15	50	15
7607 OLP	40	18	3/8	10	.600	15	70	22
7800 OLP	41	19	1/2	13	.750	19	50	15
7900 OLP	44	20	3/4	19	1.075	27	25	8
<b>Medium Pressure Oil Reels</b> Maximum Temperature 210 °F (99 °C)								
7600 OMP	43	20	3/8	10	.690	18	50	15
7800 OMP	43	20	1/2	13	.820	21	50	15
<b>High Pressure Grease Reels</b> Maximum Temperature 210 °F (99 °C)								
7400 OHP	43	20	1/4	6	.580	15	50	15
7600 OHP	46	21	3/8	10	.730	19	50	15

**NEW!**

**Reel Covers**

See page 41



**Interactive Reel Catalog**

Visit [reelcraft.com/catalog](http://reelcraft.com/catalog) for complete product specifications, parts, and accessories.



**Pivot Bases & Swing Brackets**

See page 43