



GP300™

GP Series

EPDM Rubber General Purpose Air & Water Hose

GENERAL APPLICATIONS

- Air and water service in industrial, construction, and agricultural applications
- Air compressors
- Pneumatic tools
- Spray equipment
- Low-pressure transfer of non-corrosive liquids

CONSTRUCTION

Tube – Black EPDM
 Reinforcement – Braided polyester yarn
 Cover – Black or Red EPDM

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +212°F (+100°C)

FEATURES AND ADVANTAGES

- **Durable Construction** – Long-lasting, resistant to wear, ozone, and hydrocarbons.
- **Uniform 300 PSI** – All sizes rated to 300 PSI for safety.
- **Braided-Construction Quality** – Stable under pressure with minimal expansion and twisting.

PACKAGING

Maximum 2 pcs. on reel
 1/4" – 1 1/2" ID hoses supplied on plastic reels
 2" ID hoses supplied on wooden reels

View Up To Date Info



◀ SCAN OR VISIT
[KOA.link/
 GP](https://KOA.link/GP)

SAFETY FACTOR

3:1

BRANDING

KURIYAMA GP300™ AIR & WATER GP-
 BK ID WP 300 PSI

Part Number	Color	ID (in)	ID (mm)	OD (in)	OD (mm)	Max. Working Pressure (psi)	Total Reel Length (ft)	Packaging (lengths per reel)	Weight (lbs/ft)
GP-BK025X500	Black	1/4	6	33/64	13.0	300	500	1 x 500'	0.101
GP-BK031X500	Black	5/16	8	19/32	15.0	300	500	1 x 500'	0.128
GP-BK038X500	Black	3/8	10	22/32	17.5	300	500	1 x 500'	0.170
GP-BK050X600	Black	1/2	13	53/64	21.3	300	600	2 x 300'	0.229
GP-BK062X600	Black	5/8	16	15/16	24.0	300	600	2 x 300'	0.254
GP-BK075X600	Black	3/4	19	1 5/32	29.5	300	600	2 x 300'	0.397
GP-BK100X600	Black	1	25	1 13/32	36.0	300	600	2 x 300'	0.512
GP-BK125X200	Black	1 1/4	32	1 25/32	45.2	300	200	2 x 100'	0.811
GP-BK150X200	Black	1 1/2	38	2 1/8	54.0	300	200	2 x 100'	1.151
GP-BK200X200	Black	2	51	2 19/32	66.0	300	200	2 x 100'	1.396
GP-RD025X500	Red	1/4	6	33/64	13.0	300	500	1 x 500'	0.101
GP-RD031X500	Red	5/16	8	19/32	15.0	300	500	1 x 500'	0.128
GP-RD038X500	Red	3/8	10	22/32	17.5	300	500	1 x 500'	0.168
GP-RD050X600	Red	1/2	13	53/64	21.3	300	600	2 x 300'	0.227
GP-RD062X600	Red	5/8	16	15/16	24.0	300	600	2 x 300'	0.251
GP-RD075X600	Red	3/4	19	1 5/32	29.5	300	600	2 x 300'	0.395
GP-RD100X600	Red	1	25	1 13/32	36.0	300	600	2 x 300'	0.507
GP-RD125X200	Red	1 1/4	32	1 25/32	45.2	300	200	2 x 100'	0.803
GP-RD150X200	Red	1 1/2	38	2 1/8	54.0	300	200	2 x 100'	1.140
GP-RD200X200	Red	2	51	2 19/32	66.0	300	200	2 x 100'	1.382

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.