

Single Receptacle Power Cord Reels

| Model with cord & bumper | Cord Ending | Cord Specifications | | | | | Volts Amps | | Shipping Weight | | Size Index # | |
|--------------------------|--|---------------------|-----------------|--------|-----|----|------------|-----|-----------------|-----|--------------|----|
| | | AWG | mm ² | # Cond | ft | m | Type* | | | lbs | | kg |
| L 4050 163 3 | Single receptacle NEMA 5-15R, Inlet straight blade plug NEMA 5-15P | 16 | 1.33 | 3 | 50 | 15 | SJTOW | 125 | 13 | 26 | 12 | 1 |
| L 4545 123 3 ★ | | 12 | 3.32 | 3 | 45 | 14 | SJE00W | 125 | 15 | 27 | 12 | 1 |
| L 5550 123 3 | | 12 | 3.32 | 3 | 50 | 15 | SJE00W | 125 | 15 | 44 | 20 | 3 |
| L 70075 123 3 | | 12 | 3.32 | 3 | 75 | 23 | SE00W | 125 | 15 | 70 | 32 | 5 |
| L 70100 123 3 | | 12 | 3.32 | 3 | 100 | 30 | SE00W | 125 | 15 | 74 | 34 | 5 |
| L 4525 123 3A | Single receptacle NEMA 5-20R, Inlet straight blade plug NEMA 5-20P | 12 | 3.32 | 3 | 25 | 8 | SJE00W | 125 | 20 | 25 | 11 | 1 |
| L 4545 123 3A ★ | | 12 | 3.32 | 3 | 45 | 14 | SJE00W | 125 | 20 | 28 | 13 | 1 |
| L 5550 123 3A | | 12 | 3.32 | 3 | 50 | 15 | SJE00W | 125 | 20 | 44 | 20 | 3 |
| L 70075 123 3A | | 12 | 3.32 | 3 | 75 | 23 | SE00W | 125 | 20 | 70 | 32 | 5 |
| L 70100 123 3A ★ | | 12 | 3.32 | 3 | 100 | 30 | SE00W | 125 | 20 | 74 | 34 | 5 |
| L 4545 123 3AC | Single receptacle NEMA 5-20R, Inlet twist lock plug NEMA L5-20P | 12 | 3.32 | 3 | 45 | 14 | SJE00W | 125 | 20 | 28 | 13 | 1 |
| L 70075 123 3AC | | 12 | 3.32 | 3 | 75 | 23 | SE00W | 125 | 20 | 70 | 32 | 5 |
| L 4545 123 3B | Twist lock single receptacle NEMA L5-20R, Inlet straight blade plug NEMA 5-20P | 12 | 3.32 | 3 | 45 | 14 | SJE00W | 125 | 20 | 28 | 13 | 1 |
| L 5550 123 3B | | 12 | 3.32 | 3 | 50 | 15 | SJE00W | 125 | 20 | 44 | 20 | 3 |
| L 70100 123 3B | | 12 | 3.32 | 3 | 100 | 30 | SE00W | 125 | 20 | 74 | 34 | 5 |

For indoor non-weathertight applications only. All models UL listed at 125 Volt 60 HZ single phase. Swing brackets or pivot bases should be used if cords are pulled at more than 45°, see page 39. *Cord type designation shows all combinations of cord types that may be used, only UL approved cord types will be used.

Many more cord reel models available in addition to the charts on pages 27-30. Contact Reelcraft for more information. *Minimum order quantities may apply

Refer to page 30 for dimensional drawings for all cord reels.

Models with a ★ icon are our most popular models.



L 5550 123 3A



Cord End Specifications

| | | |
|--|--|---|
| | | #3 - Single Receptacle Single 15 AMP with clamp type strain relief for 16 and 12 AWG cord. NEMA 5-15R |
| | | #3A/3AC - Single Receptacle Single 20 AMP. NEMA 5-20R |
| | | #3B - Twist Lock Receptacle Single 20 AMP with twist lock connector. NEMA L5-20R |

Reel Covers **NEW!**

Available for Series L 70000 reels only. See page 36



Flying Lead and Bare Power Cord Reels



| Model | Cord Ending | Cord Specifications | | | | | Volts/ Amps | Volts/ Amps | Shipping Weight* | | Size Index # | |
|---------------|-------------|---------------------|-----------------|--------|-----|----|-------------|-------------|------------------|----|--------------|---|
| | | AWG | mm ² | # Cond | ft | m | | | Type** | | | |
| L 4050 163 X | Flying lead | 16 | 1.33 | 3 | 50 | 15 | SJE00W | 125 / 13 | 220 / 6.5 | 26 | 12 | 1 |
| L 4545 123 X | | 12 | 3.32 | 3 | 45 | 14 | SJE00W | 125 / 20 | 220 / 10 | 25 | 11 | 1 |
| L 5550 123 X | | 12 | 3.32 | 3 | 50 | 15 | SJE00W | 125 / 20 | 220 / 10 | 35 | 16 | 3 |
| L 70100 123 X | | 12 | 3.32 | 3 | 100 | 30 | SE00W | 125 / 20 | 220 / 10 | 73 | 33 | 6 |
| L 5550 124 X | | 12 | 3.32 | 4 | 50 | 15 | SE00W | ----- | 600 / 16 | 43 | 20 | 3 |
| L 70100 124 X | | 12 | 3.32 | 4 | 100 | 30 | SE00W | ----- | 600 / 16 | 75 | 34 | 6 |
| L 5750 103 X | | 10 | 5.27 | 3 | 50 | 15 | SE00W | 125 / 30 | 220 / 15 | 55 | 25 | 4 |
| L 7050 104 X | | 10 | 5.27 | 4 | 50 | 15 | SE00W | ----- | 600 / 20 | 65 | 29 | 7 |
| L 4500 | Bare reel | 12 | 3.32 | 3 | 45 | 14 | SJE00W | 125 / 20 | 220 / 10 | 21 | 10 | 1 |
| L 70100 | | 12 | 3.32 | 3 | 100 | 30 | SE00W | 125 / 20 | 220 / 10 | 58 | 26 | 6 |
| L 70100 124 | | 12 | 3.32 | 4 | 100 | 30 | SE00W | ----- | 600 / 16 | 75 | 34 | 6 |
| L 5000 | | 10 | 5.27 | 3 | 35 | 11 | SO | 125 / 30 | 220 / 15 | 29 | 13 | 2 |
| L 5700 | | 10 | 5.27 | 3 | 50 | 15 | SE00W | 125 / 30 | 220 / 15 | 37 | 17 | 4 |
| L 7000 | | 6 | 13.3 | 4 | 35 | 11 | SOOW | ----- | 220 / 45 | 41 | 19 | 7 |

For indoor non-weathertight applications only. All models UL listed at 125/220 Volt 60 HZ single phase. Swing brackets or pivot bases should be used if cords are pulled at more than 45°, see page 39. Flying lead models include cord and bumper. **Equivalent cord type may be used.



L 70100 123 X



Cord End Specifications

| | |
|--|---|
| | X - Flying Lead Flying leads on inlet and outlet and conduit box. |
|--|---|